

**Your unique kitchen – tailored to suit you**

Combine this modular hob with other modular hobs from Electrolux to build your own tailored mix of cooking methods – choose from gas, induction and radiant.

**Product Benefits & Features****A reliable tool for everyday cooking**

This gas hob is the perfect everyday tool for daily cooking. It's simple and reliable and will help make sure that cooking is always a pleasure.

- Hob type: Gas
- Rotary knob controls
- Controls position: Front
- Left front zone: No, 0W/0mm
- Left rear zone: No, 0W/0mm
- Middle front zone: Auxiliary Burner, 1000W/54mm
- Middle rear zone: Rapid Burner, 3000W/100mm
- Right front zone: No, 0W/0mm
- Right rear zone: No, 0W/0mm
- Gas conversion kit
- Main colour: Stainless Steel

**A natural movement, all the way from low heat to high**

At the front of this hob are the rotary control knobs. They're designed to be easy to twist and turn when you change the power levels of your hob.

**A practical solution gives you peace of mind**

If the flame of your gas burner is accidentally blown out, this hob's innovative technology can detect it, and automatically cut off the gas supply.

**Automatic hob ignition allows you to get started without delay**

By cleverly combining heat control and the ignition in one push-and-twist button, you can fire up your hob instantly and get cooking in no time.

**Product Specification**

Product Installation	Built_In	Gas category	I12H3+
Product Typology	Gas_Hob	Frequency	50-60
Product Classification	Core	Voltage	220-240
Installation	Independent	Cord length external	1.1
Size	Domino	Type of plug	No
Hob type	Gas	Connector type	Cylinder gas elbow
Design family	BlueFire		
Main colour	Stainless Steel		
Control Panel material	Monopressed		
Knobs colour	Stainless Steel		
Top Control Place	Front		
Type of controls	Knobs		
Control function	No		
Other comments design	new Electrolux spin effect knob duplication of PNC 949 738 223, ITALIAN MARKET, Denomination alignment		
Other comments categorisation			
Width mm	290		
Depth mm	510		
Built in height mm	30		
Width cutting	270		
Depth cutting	490		
Fastening	Fixing Clamps		
Gas original	G20 (2H) 20 mbar		
Gas replacement 2	G30/G31 (3+) 28-30/37 mbar		
Gas replacement 3	No		